



## SINGLE FAMILY RESIDENCE HURRICANE MITIGATION APPLICATION

**Job Address:** \_\_\_\_\_

Florida Statute 553.844 requires that certain hurricane mitigation upgrades must be performed when a detached single family residence is being re-roofed. Required upgrades include the installation of roof to wall connections, when the house was built prior to 1994, has a value of \$300,000.00 or more (excluding land value) and the existing connections are less than an 1/8" by 1" strap, attached with (3) 16 d nails. Re-nailing of roof sheathing and the installation of a secondary water barrier are also required. The following must be completed to confirm compliance with these requirements.

**A. Was the dwelling permitted on or after 1994?**    Yes    No  
If yes, provide the year: \_\_\_\_\_.

**If you answered yes, proceed to part E; and leave parts B, C, then proceed to part D as applicable.**

**If you answered No, then fill out part B or C, then proceed to part D as applicable.**

**B. As demonstrated by the attached documentation, the insured value of the house is:**  
\$\_\_\_\_\_.

**C. The insured value of the house is not available; attached is copy of the Broward County Property Appraisers' Ad-valorem value, which is:** \$\_\_\_\_\_.

**D. If the value is \$300,000 or more, the following must be provided, prior to obtaining a re-roofing permit:**

The following Engineer, Architect, Contractor (General, Building, Residential) or Private Structural Inspector has been retained to provide the required roof to wall certification:

Name: \_\_\_\_\_

License Type: \_\_\_\_\_ License Number: \_\_\_\_\_

Business Name: \_\_\_\_\_ Phone Number: \_\_\_\_\_

Business Address:  
\_\_\_\_\_  
\_\_\_\_\_

We understand that a separate permit is required if the existing connections are not adequate. The following Contractor (General, Building, Residential) has been retained for this work:

Name: \_\_\_\_\_

License Type: \_\_\_\_\_ License Number: \_\_\_\_\_

Business Name: \_\_\_\_\_ Phone Number \_\_\_\_\_

Business Address:

\_\_\_\_\_  
\_\_\_\_\_

**E.** The following secondary water barrier will be utilized (roofing application includes applicable documentation):

- 4 inches 40 mil polymer strip ASTM D 1970 on all sheathing joints, or
- An approved self-adhering polymer modified bitumen cap sheet, or
- An approved hot mopped cap sheet.
- 30 lbs felt underlayment per HVHZ.

\_\_\_\_\_  
Signature of Roofing Company Qualifier

\_\_\_\_\_  
Roofing Company Name

\_\_\_\_\_  
Print Name

\_\_\_\_\_  
Date